

SCHÜCO

PREMIUM PARTNER

**PROFILE SYSTEM
FOCUSING****DESIGN**

Modern, straight contours and minimal overlaps blend seamlessly into the minimalist construction trend.

**THERMAL
INSULATION**

Maximum performance through the five- or six-chamber profile constructions with two sealing levels.

**SUSTAINABILITY**

A high recycled content in the inner core ensures a resource-saving use of materials.

**SYSTEM
COMPATIBILITY**

Perfect compatibility with other Schüco products for seamless integration.

**DIVERSE
COLORS**

A wide range of color options for individual design and customization.

**RESILIENCE**

Robust, long-lasting construction for maximum stability and durability.

SCHÜCO

PREMIUM PARTNER

PROFILE SYSTEM FOCUSING

Suitable for:

**BREEAM®**

TECHNICAL DATA

Basic depth outer frame	70 mm
Basic depth vent	76 mm
Uw value	0,82 W/(m²K)*
Glass thickness outer frame	10–48 mm
Glass thickness vent	16–54 mm
Max. vent width**	1500 mm
Max. vent height**	2600 mm
Max. sound reduction index Rwp	48 dB(A)
Air permeability	Class 4
Watertightness	Class 9A
Burglar resistance	up to RC 2
Wind load resistance	Class B5
Max. vent weight	120 kg



Operating forces	Class 1
Mechanical strength	Class 4, DIN EN 13115
Proof of durability	DIN EN 12400, Class 2
Drainage levels	2

* in version with Ug 0.5 glazing

** Maximum dimensions only possible with correct height-to-width ratio

More info:

<https://www.schueco.com/de-en/architects/products/windows/pvc-u/focusing>



up
FENSTER & TÜREN