

PREMIUM PARTNER

**PROFILE SYSTEM** 



#### **PURE LIVING COMFORT**

The innovative Schüco LivIng Alu Inside system sets new standards not only in energy-efficient window technology but also provides noticeable protection against cold, noise, and drafts.



# **UNIQUE TECHNOLOGY**

By using unique aluminum composite technology, this profile system delivers top-level thermal insulation and achieves maximum stability and strength in all areas even without steel reinforcement in the core.

### **TOP INSULATION VALUES**

With a Uw value of 0.70 W/(m2K). LivIng Alu Inside is a passive house-compatible profile system - ideal for energy-efficient construction and low heating costs.



# SUSTAINABLY **DESIGNED**

The system is particularly durable and fully recyclable ideal for sustainable construction.

## **NOTICEABLE OUIETNESS**

The profile system achieves, with appropriate soundproof glazing, a sound insulation of up to 46 dB - for noticeably better living quality.



#### **DESIGN FLEXIBILITY**

Individual color options, modern sash geometries, and large glass surfaces -LivIng makes design wishes come true.





PROFILE SYSTEM LIVING ALU INSIDE

#### Suitable for:















# **TECHNICAL DATA**

Basic depth outer frame	82 mm
Basic depth vent	82 mm
Uw value (	).70 W/(m²K)*
Glass thickness outer frame	16-52 mm
Glass thickness vent	16-52 mm
Max. vent width**	1500 mm
Max. vent height**	2600 mm
Max. sound reduction index I	<b>Rwp</b> 46 dB(A)
Air permeability	Class 4
Watertightness	Class 9A
Burglar resistance	up to RC 2
Wind load resistance	Class C5/B5
Max. vent weight	120 kg



Operating forces	Class 1
Mechanical strength	Class 4, DIN EN 13115
Proof of durability	DIN EN 12400, Class 2
Drainage levels	3 (central sealing system)

- in version with Ug 0.6 glazing and with insulating wedges
  Maximum size only possible with correct height and aspect ratio

#### More info:

https://www.schueco.com/de-en/architects/ products/windows/pvc-u/living-alu-inside



